

ACO. we care for water



Qmax Neo 600 Channel

a new dimension in the Qmax family

Product information

- 4-times higher cross-section area than Neo 300
- Easy combination with other sizes of the Qmax family
- Traffic loads from A15 to F900
- Large choice of material for edge rail

ACO Product Benefits

- Lightweight product / Easy handling
- Space saving transport / Assembling on-site
- Click-on assembly / Quick solution
- Integrated seal / Plug-in installation
- Liquid tight channel run / Chemical resistant



Typical applications of use:

- Airports
- Logistic centres
- Industrial Areas

ACO Qmax Neo 600

Assembly of Qmax Neo 600 with cast iron rail consists of:



Part description

Product	PCS/ 1m assembly	PU (pcs)	Note	Item No.
ACO Qmax Neo 600 bottom half	1	11	With longitudinal gasket	157301
ACO Qmax Neo 600 upper half	1	11	With longitudinal gasket	157302
ACO Qmax sealing for NEO 600	1	80	-	157407

Optional rail

ACO QFlow cast iron rail 0,5 m	2	80	-	157411
ACO QGuard cast iron rail 0,5 m	2	80	-	157412

Optional inlet

ACO Qmax Neo Inlet 200		2	80	For A15 + B125 Load class	157403
ACO Qmax Neo Inlet 400		2	80	For C250 to F900 Load class	157406

Neo 600 Accessories

ACO Qmax Neo 600 - Leveling feet	-	120	-	157307
Screw	-	-	Necessary for Leveling feet	157419
ACO Qmax Neo 600 - End Cap	-	-	-	418594
ACO Qmax Neo 600 - Double Fitting	-	-	-	418595
ACO Qmax Neo Step connector 300/600	-	-	For the same inlet size only	418593

Standard access chamber solution with outlet connection DN300

Standard access chamber	Item No.
Qmax 600 access chamber male - female	418590
Qmax 600 access chamber female - male	418591
Qmax 600 access chamber female - female	418592

*Customized solution of access chamber on request.

Access chamber can be configured by configurator on **ACO Product Configurator**

